

CLOCK Ø 120 mm 220-250V

datasheet

CODE NO. **4665**

GM GM = Metallized grey


GR GR = Graphite


3K – 3000K / **4K** – 4000K

Ø 120 mm

36 mm

136 mm



LAMP	LED
NOMINAL LUMEN	1575
REAL LUMEN OUTPUT	1050
WATTAGE	15W
VOLTAGE	220-240V 50/60Hz
IP	IP 67
IK	IK08 (6 joules)
CLASS	 Classe I
CERTIFICATION	
CONFORMITY	EN 60598-1 +2-1
ENERGY CLASS	F

Watertight spotlight, to be installed on the wall, on a stem or on an earth spike in the garden

Structure: body and arm made of primary aluminium alloy with low copper content

Adjustable light body with stable fastening in the chosen point

Ultrawhite transparent tempered glass, sealed to the frame

Wiring: the spotlight is hermetically sealed with a two-component resin and provided with a 1,5 m H05RN-F buriable cable. The cable can pass through a special hole in the base of the arm

Mains voltage LED module, compatible with most phase-cut dimmers / CRI≥80

Beam angles: 12° (option) / 40° (standard) / 90° (option) / 10° honeycomb (option - add HC to the code)

Double varnished finish after pickling, chromic passivation (trivalent chromium), epoxy primer and polyester powder coating

RGBW version: see RGBW series - code 1187

ON REQUEST:

2700K LED color temperature (code + 27K)

12-24V low voltage version (code + LV)

7 m cable length (code + MT7)

Finishing colours: BI - white / CO - corten